

ODS-AGM28L (PC925)

Technical Data Sheet

Battery Type

AGM with Thin Plate Pure Lead (TPPL). Advanced dual-purpose battery for engine start and deep-cycle use

Power & Performance

Voltage	12V	
Capacity (20-hour rate)	28Ah	
Capacity (10-hour rate)	27Ah	
Cold Cranking Amps (CCA, SAE J537)	330A	
PHCA - 5-second pulse current	900A	
HCA	610A	
MCA	480A	
Reserve capacity	48 mins	
Short circuit current (using IEC method)	2400A	
Internal resistance at 20°C (using IEC method)	$5~\text{m}\Omega$	

Dimensions & Weight

Length	168 mm
Width	175 mm
Height (to top of terminals)	119 mm
Height Container	127 mm
Weight	10.8 kg

Temperature

Operating Temperature Range	-40°C to +50°C
Optimum Storage Temperature	+20°C

Accreditations

The management systems governing the manufacture of this product are ISO 9001 and ISO 14001 certified.

Charging & self-discharge

Type of charging curve	100
Charge voltage @+20°C	14.4V to 14.8V
Self-discharge per month at +20°C	1.25%
Self-discharge per month at +40°C	5%

Fitting, handling & storage

Can be mounted or stored in any orientation except inverted. 2-years storage life at +20°C without charging, or until the Open Circuit Voltage (OCV) is <12.6V or <2.10Vpc, whichever occurs first. Classified as non-spillable and approved as non-hazardous cargo for ground, sea and air transportation in accordance with the requirements of IMDG (International Maritime code for dangerous Goods) and ICAO (International Civil Aviation Organisation).

PDF Generated at https://eu.odysseybattery.com 09/05/2022 11:13:28 Information correct at time of exporting PDF. Please check website for updates.




EnerSysWorld Headquarters 2366Bernville Road Reading, PA 19605,USA Tel: +1-610-208-1991 /


EnerSys EMEA EH Europe GmbH Baarerstrasse 18 6300Zug.

EnerSys Asia 152 Beach Road Gateway East Building #11-08 Singapore 189721 Tel: +65 6508 1780



Terminal Position





ODS-AGM28L RIGHT POSITIVE FEMALE TERMINAL

Terminal Type

